

Enphase Three-Phase Network Protection Relay

(NPR-3P-208-NA)

The **Enphase Three-Phase Network Protection Relay™** with Enphase IQ Envoy™ gateway and Enphase Mobile Connect™ modem consolidates three-phase interconnection equipment into a single enclosure and streamlines installations by providing a consistent, pre-wired solution for three-phase commercial 208 VAC applications.



Smart

- Compatible with single-phase Enphase IQ 7™ Series Microinverter-based, three-phase commercial 208 VAC PV systems
- Includes IQ Envoy for PV system communication and control
- CTs for phase-wise production monitoring (optional)
- Flexible networking supports Wi-Fi, Ethernet, or cellular (standard)

Simple

- Built-in network protection relay and contactor
- Compact enclosure with pre-wired system components
- Backplate for easy mounting
- Customizable cable entry/exit options for quicker installation
- Can accommodate 200A three-phase AC input

Reliable

- Durable NEMA type 3R enclosure
- Five-year warranty
- Compliant with UL 1741 SA



To learn more about Enphase offerings, visit enphase.com

Enphase Three-Phase Network Protection Relay

MODEL NUMBER	
Three-Phase Network Protection Relay (NPR-3P-208-NA)	Three-Phase Network Protection Relay with Enphase IQ Envoy™ gateway and Enphase Mobile Connect modem and contactor for three-phase network monitoring
ENPHASE ACCESSORIES and REPLACEMENT PARTS	
Enphase Mobile Connect™ CELLMODEM-M1 (4G based LTE-M)	Plug and play industrial grade cellular modem with data plan options ¹ (available in the US, Canada, Mexico, Puerto Rico, and the US Virgin Islands, where there is adequate cellular service in the installation area)
Enphase IQ Envoy™ ENV-IQ-AM3-3P	Three-phase communications gateway with integrated PV production metering (+/- 0.5%) and optional consumption monitoring (+/- 2.5%). Includes three 200A continuous rated production CTs.
Consumption Monitoring* CT CT-200-SPLIT (not included - three needed)	Split core current transformers enable consumption metering (+/- 2.5%)
COMPONENTS	
Relay, SEL-547	Distributed generator interconnection relay with essential network protection and control elements for three-phase commercial solar PV systems
Contactor, AF190 or AF205	Minimum: AC-1, 200 A, 3P, NO MAIN + 1 NO and 1 NC AUX, 24-60 VAC/DC coil
Distribution Block, L1, L2, L3	3-P, (2) 250 kcmil – 1/0 AWG
Distribution Block, Neutral	1-P, (2) 250 kcmil – 1/0 AWG
Ground Lug, Grid and Array	(1) 250 kcmil - #6 AWG
Interconnections	Pre-wired internal interconnections
ELECTRICAL SPECIFICATIONS	
Rating	Continuous operation at 100% of rating
Rated voltage	Three-phase 208/120 VAC, 60 Hz
Rated current	200 A
Rated breaker size	250 A maximum
PV array conductors	L1, L2, L3, N, 250 kcmil – 1/0 AWG and G, 250 kcmil - #6 AWG
Grid conductors	L1, L2, L3, N, 250 kcmil – 1/0 AWG and G, 250 kcmil - #6 AWG
MECHANICAL DATA	
Enclosure dimensions	610 mm x 762 mm x 254 mm (24" x 30" x 10")
Weight	34.5 kg (76 lbs)
Ambient temperature range	-25° C to +50° C (-13° to 122° F)
Enclosure environmental rating	Outdoor, NEMA type 3R
INTERNET CONNECTION OPTIONS	
Integrated Wi-Fi	802.11b/g/n
Cellular (standard)	CELLMODEM-M1 (4G based LTE-M) with data plan options ¹
Ethernet	Optional, 802.3, Cat5E (or Cat 6) UTP Ethernet cable (not included)
COMPLIANCE	
Loss of phase	IEEE 1547:2018; CA Rule 21, HI Rule 14h, LVRT up to 2 seconds
Safety	UL 1741

1. Contact Enphase for data plan options.

To learn more about Enphase offerings, visit enphase.com

© 2020 Enphase Energy. All rights reserved. Enphase, the Enphase logo, IQ Envoy, Mobile Connect, and other trademarks or service names are the trademarks of Enphase Energy, Inc. Data subject to change. 2020-03-26

